

WORKSHOP HOSES | REELS | ACCESSORIES | WORK GEAR











THE BIUSIFO ADVANTAGE...

SOPHISTICATED. INNOVATIVE. TRUSTED.

Designed with professionals in mind, BluBird delivers high-performance hose solutions that combine innovation, durability, and exceptional value. With over 30 years of industry expertise, BluBird has developed a full line of advanced general-purpose hoses and retractable metal hose reels—engineered to withstand extreme environments and meet the demands of users around the globe.

BluBird is the only manufacturer in the world producing both its hoses and the reels they're paired with—ensuring seamless integration, top-tier quality, and industry-leading performance. Built on decades of R&D, BluBird's technology sets the standard for flexibility, strength, and ease of use. From extreme cold to intense heat, BluBird hoses deliver unmatched reliability in any condition.



















40% LIGHTER than Standard Rubber Air Hoses 100% RUBBER

Safest | Strongest | Most Flexible

300 PSI Working Pressure 1200 PSI Burst Pressure 4.1 Safety Factor Pressure

BluBird hoses are 40% lighter, stronger, and more flexible than standard rubber hoses. They offer superior cold weather flexibility, performing reliably in temperatures as low as -50°F and maintaining their integrity up to +190°F, making them ideal for year-round use in most parts of the world.

Each BluBird hose features an abrasion-resistant outer cover, high-strength woven polyester reinforcement to prevent elongation, and industrial-grade thread and yarn for added durability. This construction delivers a 300 PSI working pressure and a 4:1 safety burst ratio, setting a new standard for performance and reliability.

- Solid brass fittings offer superior durability and corrosion resistance compared to aircraft-grade aluminum.
- High-strength polyester braided reinforcement provides exceptional burst resistance and structural integrity.
- Maintains flexibility and performance

- even under extreme weather conditions — from freezing cold to intense heat.
- Ozone-resistant for enhanced longevity in outdoor environments.
- Abrasion-resistant outer cover protects against wear and tear.
- Kink-resistant design ensures uninterrupted airflow



SUPERIOR **COLD WEATHER** FLEXIBILITY.







REFERENCE	DESCRIPTION	BORE	LENGTH	FITTING
311 2708	Whip Hose (Heavy-Duty)	6mm (1/4")	0.6m (2ft)	1/4" F-NPT + 1/4" M-Ball Swivel
311 3236	Whip Hose (Heavy-Duty)	13mm (1/2")	0.6m (2ft)	1/2" F-NPT + 1/2" M-Ball Swivel
311 3292	Air Hose (Heavy-Duty)	6mm (1/4")	20m (66ft)	x2 1/4" M-NPT (+ Coupling Set)
311 2617	Air Hose (Heavy-Duty)	10mm (3/8")	10m (33ft)	x2 3/8" NPT + 1/4" Reducer
311 2603	Air Hose (Heavy-Duty)	10mm (3/8")	20m (66ft)	x2 3/8" NPT + 1/4" Reducer
311 3229	Air Hose (Heavy-Duty)	13mm (1/2")	10m (33ft)	x2 1/2" M-NPT + 3/8" Reducer
311 2610	Air Hose (Heavy-Duty)	13mm (1/2")	20m (66ft)	x2 1/2" M-NPT + 3/8" Reducer
311 3285	Air Hose Reel (Heavy-Duty)	13mm (1/2")	15m (49ft)	x2 1/2" M-NPT+ 3" Lead-In Hose
311 3271	Air Hose Reel Dual Arm (Heavy-Duty)	10mm (3/8")	30m (98ft)	x2 3/8" NPT+ 3" Lead-In Hose
311 2638	Swivel Mount for Hose Reel			180° H:6.8" x W:8.5" x D:2.6"

GET IN TOUCH IF YOUR DESIRED SIZE IS NOT LISTED...



30% LIGHTER than Standard **Rubber Air Hoses**

RMA Class A Oil Resistant Air Hose

100% RUBBER



300 PSI Working Pressure 1200 PSI Burst Pressure 4:7 Safety Factor Design

Oil-Shield® sets the standard as the best-performing shop hose on the market today. Made from 100% rubber with a Nitrile core and Nitrile outer cover, it delivers a Class A oil-resistance rating—the highest rating possible.

Unlike traditional rubber hoses that are heavy and inflexible, Oil-Shield is 30% lighter, more flexible, and stronger, making it easier to handle without sacrificing durability. It's engineered to perform in demanding workshop environments, offering reliable resistance against oil, diesel, gasoline, cleaning agents, and even welding spatter and grinding sparks.

- RMA Class A oil-resistant core tube and cover — the highest level of oil resistance available
- Resists welding spatter and grinding sparks — ideal for tough shop environments
- Solid brass fittings more durable and corrosion-resistant than aircraft aluminum

- High-strength polyester braided reinforcement – prevents elongation and enhances durability
- Maintains flexibility and integrity in extreme temperatures and working conditions
- Ozone-resistant built to withstand outdoor exposure without cracking

SPARK, WELD & OIL RESISTANT.



REFERENCE	DESCRIPTION	BORE	LENGTH	FITTING
311 3278	Air Hose (Heavy-Duty)	8mm (1/4")	20m (66ft)	x2 1/4" M-NPT
311 3145	Air Hose (Heavy-Duty)	10mm (3/8")	20m (66ft)	x2 3/8" M-NPT 1/4" Reducers
311 3152	Air Hose (Heavy-Duty)	13mm (1/2")	15m (49ft)	x2 1/2" M-NPT 3/8" Reducers
311 3166	Air Hose Reel (Heavy-Duty)	10mm (3/8")	15m (49ft)	x2 3/8" M-NPT+ 3" Lead-In Hose
311 3159	Air Hose Reel (Heavy-Duty)	13mm (1/2")	10m (33ft)	x2 1/2" M-NPT+ 3" Lead-In Hose
311 2638	Swivel Mount for Hose Reel			180° H:6.8" x W:8.5" x D:2.6"





Light Weight & Super Strong

20% LIGHTER than Standard Rubber Air Hoses

100% RUBBER



Flexibility in extreme

300 PSI Working Pressure 1200 PSI Burst Pressure 4. Safety Factor Pressure

Avagard represents the next generation of the classic red rubber hose. Unlike traditional rubber hoses that tend to be heavy and stiff, Avagard is engineered to be 20% lighter while delivering superior flexibility and strength. This innovative design makes it easier to handle without sacrificing durability. Built to withstand demanding conditions, Avagard hoses come with an unmatched 5-year warranty, reflecting the confidence in their long-lasting performance. Offering a perfect balance between quality and affordability, Avagard provides excellent value at a competitive mid-range price point — making it the smart choice for both professional and everyday use.

- Solid brass fittings superior to aircraft-grade aluminum
- High-strength polyester woven braided reinforcement for maximum durability
- Maintains structural integrity under extreme weather conditions
- Flexible from -40°C to +88°C
- Ozone resistant for long-lasting performance

- Abrasion resistant to withstand rough
- Kink resistant for uninterrupted flow
- Four Finger Grip Bend Restrictor enhances control and reduces wear for easier handling



THE EVOLUTION OF THE OLD FASHIONED RED RUBBER HOSE.







REFERENCE	DESCRIPTION	BORE	LENGTH	FITTING
RG6 0000	Air Hose	6mm (1/4")	15m (49ft)	x2 1/4" M-NPT
RG6 0002	Air Hose	8mm (1/4")	15m (49ft)	x2 1/4" M-NPT
RG6 0004	Air Hose	10mm (3/8")	15m (49ft)	x2 3/8" M-NPT + 1/4" Reducers
RG6 0020	Air Hose	10mm (3/8")	15m (49ft)	x2 3/8" NPT + 1/4" Reducers (+ Couplings)
RG6 0006	Air Hose	13mm (1/2")	15m (49ft)	x2 1/2" M-NPT + 3/8" Reducers
RG6 0025	Air Hose	13mm (1/2")	15m (49ft)	x2 1/2" M-NPT + 3/8" Reducers (+ Couplings)
RG6 0030	Air Hose Reel	10mm (3/8")	20m (66ft)	x2 3/8" M-NPT+ 3" Lead-In Hose
RG6 0035	Air Hose Reel	13mm (1/2")	15m (49ft)	x2 1/2" M-NPT+ 3" Lead-In Hose
311 2638	Swivel Mount Hose Reel			180° H:6.8" x W:8.5" x D:2.6"



LIGHTER than Standard **Polyvinyl Air Hoses & OIL RESISTANT!**

Extremely Durable PVC Air Hose Kit

300 PSI Working Pressure 1200 PSI Burst Pressure 4.7 Safety Factor Design



LIGHTER than Standard Polyurethane Air Hoses **& OIL RESISTANT!**

Premium Polyurethane Air Hoses



300 PSI PSI Burst Nylon Spiral Reinforcement

KIT INCLUDES...

Avagard* PVC Air Hose. Safety Blow Gun (x1). Tire Gauge(x1), Air Chuck (x1). Male Plugs Industrial Style 1/4" NPT (x3). Female Plugs Industrial Style 1/4" NPT (x2), Male Coupler Industrial Style 1/4* NPT (x1). Female Coupler Industrial Style 1/4* NPT (x1). Teflon Tape (x1), Storage Bag (x1).



REFERENCE	DESCRIPTION	BORE	LENGTH	FITTING
311 3187	13pc PVC Air Hose Kit	10mm (3/8")	15m (49ft)	x2 1/4" M-NPT

Avagard Braided Polyurethane Hoses are ideal for both indoor and outdoor use. Designed for exceptional cold-weather flexibility, they are lightweight, non-marking, and outperform traditional nylon hoses. Each hose is equipped with bend restrictors to protect the revolving fittings located on both ends.



UNMATCHED COIL INTEGRITY.

REFERENCE	DESCRIPTION	BORE	LENGTH	FITTING
311 3299	Air Hose	10mm (3/8")	20m (66ft)	x2 1/4" M-NPT
311 3173	Recoil Air Hose	6mm (1/4")	10m (33ft)	x2 3/8" Male Revolving NPT
311 3180	Recoil Air Hose	10mm (3/8")	10m (33ft)	x2 1/4" Male Revolving NPT



Rubber Water Hoses

20% LIGHTER than Standard Rubber Water Hoses 100% RUBBER



40% LIGHTER than Standard Rubber Water Hoses 100% RUBBER



Flexibility in extreme conditions from





High Strength Polyester Braided Reinforcement



Flexibility in extreme conditions from



300 PSI Burst Pressure



High Strength Polyester Braided

The Avagard Water Hose offers pro-level performance at a mid-range price. Made from 100% rubber, it's 20% lighter than standard rubber hoses while remaining tough, flexible, and durable. Rated for hot water up to 212°F, it's ideal for automotive, industrial, and general professional use. An ozone-resistant cover protects against weather, kinks, and abrasion, while braided polyester reinforcement adds strength. The Four Finger Grip Bend Restrictor improves control and reduces wear, and plated brass fittings provide secure, rust-resistant connections.





BluSeal Rubber Water Hose sets a new standard in performance, Made from 100% rubber, it's the lightest, strongest, and most flexible rubber hose available—ideal for lawn, garden, and hot water use. An ozone-resistant cover protects against weather, abrasion, and kinks, while polyester braided reinforcement ensures durability. The Four Finger Grip Bend Restrictor improves control and prevents wear at the ends, and plated brass fittings offer secure, rust-resistant connections.





REFERENCE	DESCRIPTION	BORE	LENGTH	GPM @ 65 PSI	GPM @ 35 PSI
311 3257	Water Hose	16mm (5/8")	15m (49ft)	11.90	10.30
311 3264	Water Hose	19mm (3/4")	20m (66ft)	17.10	10.90

REFERENCE	DESCRIPTION	BORE	LENGTH	GPM @ 65 PSI	GPM @ 35 PSI
311 3264	Water Hose	16mm (5/8")	15m (66ft)	11.90	10.30
311 3250	Water Hose Reel	16mm (5/8")	15m (66ft)	17.10	10.90
311 2638	Swivel Mount for Hose Reel				180° H:6.8" x W:8.5" x D:2.6"



UV, OIL, SALT & ACID RESISTANT

FEATURES...

- Non-slip ridges provide a firm, secure grip
- Ideal for environments with corrosive chemicals
- Includes an eyebolt and integrated handles for easy transport or linking multiple chocks
- Wide base enhances stability and structural rigidity
- Constructed from heavy-duty rubber for long-lasting durability



REFERENCE	DESCRIPTION	ТҮРЕ
870 5029	Wheel Chock	Single Sided with Eye Bolt
870 5139	Wheel Chock	Double Sided Pyramid with Eye Bolt



Premium Polyester Tool Bags

TEAR-RESISTANT STITCHING









REFERENCE	DESCRIPTION	DIMENSIONS (H X W X D)	CARRY	WEIGHT
RG1 0996	11 Pocket Pouch	33 cm (13") x 33 cm (13") x 6.4 cm (2.5")	10cm Belt Loop	0.6kg
RG1 0990	48 Pocket Backpack	40.6 cm (16") x 30.5 cm (12") x 25.4 cm (10")	97cm Strap	1.8kg
RG1 0992	22 Pocket Bigmouth	26.7 cm (10.5") x 31.8 cm (12.5") x 19.1 cm (7.5")	120cm Strap	1kg
RG1 0994	31 Pocket Bigmouth	27.9 cm (11") x 40.6 cm (16") x 24.1 cm (9.5")	120cm Strap	1.4kg

Get in touch! autosales@tip-top.co.uk 0113 277 0044

Westland Square · Leeds · West Yorkshire · LS11 5XS +44 (0)113 277 0044 www.rema-tiptop.co.uk















